

## SAFETY DATA SHEET

| Section 1. Chemical Product and Company Identification  |   |
|---|---|
| <b>Products Name</b>  | Rechargeable Li-ion Battery   |
| <b>Mode/Type reference</b>  | 18650 2600mAh 14.4V 37.44Wh   |
| <b>Nominal Voltage</b>  | 14.4V   |
| <b>Typical Capacity</b>   | 2200mAh   |
| <b>Typical Power</b>  | 37.44Wh   |
| <b>Manufacture Name</b>   | Dongguan Large Electronics Co.,Ltd  |
| <b>Address</b>  | No. 8 Jingyi Road, Dongcheng District, Dongguan City, Guangdong Province, China |
| <b>Postcode</b>   | 523017  |
| <b>Emergency Telephone No.</b>  | +86-769-22810105  |
| <b>Technical Support Telephone No.</b>  | +86-769-22810105  |
| <b>Fax</b>  | +86-769-22813796  |
| <b>E-mail</b>   | jcrz@juda.cn  |
| <b>Issue Date</b>   | 2021-01-01  |
| Section 2. Hazards Identification   |   |
| <b>Classification</b>   |   |
| <p>This chemical is not considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200) this product is an article which is a sealed battery and as such does not require an MSDS per the OSHA hazard communication standard unless ruptured. The hazards indicated are for a ruptured battery.</p>                |   |
| Skin corrosion/irritation   | Category 4  |
| Serious eye damage/eye  | Category4   |
| Skin sensitization  | Category3   |
| Carcinogenicity   | Category5   |
| Specific target organ toxicity (repeated exposure)  | Category3   |
| <p><b>GHS Label elements, including precautionary statements</b></p> <p style="text-align: center;"><b>Emergency Overview</b></p> <p><b>Signal word:</b> Danger</p> <p><b>Hazard Statements</b></p> <p>Causes skin irritation</p> <p>Causes serious eye irritation</p> <p>May cause an allergic skin reaction</p> <p>May cause cancer</p> |   |

**SAFETY DATA SHEET**



This product is an article which contains a chemical substance. Safety information is given for exposure to the article as sold.

Intended use of the product should not result in exposure to the chemical substance This is a battery. In case of rupture: the above hazards exist.

**Appearance:** Green

**Physical State:** Cylinder

**Odor:** Odorless

|   |   |
|---|---|
| <p><b>Precautionary Statements - Prevention</b></p>   | <p>Obtain special instructions before use<br/>                 Do not handle until all safety precautions have been read and understood<br/>                 Use personal protective equipment as required<br/>                 Wash face, hands and any exposed skin thoroughly after handling<br/>                 Contaminated work clothing should not be allowed out of the workplace<br/>                 Wear protective gloves<br/>                 Do not breathe dust/fume/gas/mist/vapors/spray<br/>                 Do not eat, drink or smoke when using this product</p>                        |
| <p><b>Precautionary Statements - Response</b></p>     | <p>IF exposed or concerned: Get medical advice/attention<br/>                 Specific treatment (see supplemental first aid instructions on this label)<br/>                 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing If eye irritation persists: Get medical advice/attention<br/>                 IF ON SKIN: Wash with plenty of soap and water<br/>                 Take off contaminated clothing and wash before reuse<br/>                 If skin irritation or rash occurs: Get medical advice/attention</p> |
| <p><b>Precautionary Statements - Storage</b></p>      | <p>Store locked up</p>  |
| <p><b>Precautionary Statements - Disposal</b></p>     | <p>Dispose of contents/container to an approved waste disposal plant</p>  |
| <p><b>Hazards not otherwise classified (HNOC)</b></p> | <p>Not applicable</p>   |
| <p><b>Unknown Toxicity</b></p>                        | <p>-</p>  |
| <p><b>Other information</b></p>                       | <p>May be harmful if swallowed Very toxic to aquatic life with long lasting effects<br/>                 Repeated or prolonged skin contact may cause allergic reactions with susceptible</p>   |

## SAFETY DATA SHEET

|  |                           |
|--|---------------------------|
|  | persons                   |
| <b>Interactions with Other Chemicals</b> | No information available. |

### Section 3. Composition/Information on Ingredients

| Chemical Name                     | CAS Number          | Weight-%    | Trade Secret |
|-----------------------------------|---------------------|-------------|--------------|
| Lithium Cobalt Dioxide            | 12190-79-3          | 12.5~13.5 % |              |
| Lithium manganate                 | 12057-17-9          | 12.5~13.5 % |              |
| Nickel(III) oxide                 | 1314-06-3           | 12.5~13.5 % |              |
| Polyvinylidene fluoride (PVdF)    | 24937-79-9          | 0.5%~1.5%   |              |
| Aluminium foil                    | 7429-90-5           | 3%~4%       |              |
| Graphite (C)                      | 7440-44-0           | 17 %~19%    |              |
| Styrene Butadiene Rubber(SBR)     | 9003-55-8           | ≤1%         |              |
| Carboxy Methylated Cellulose(CMC) | 9004-32-4           | ≤1%         |              |
| Copper foil                       | 7440-50-8           | 6.5%~7.5%   |              |
| Polyethylene (PE)                 | 9002-88-4           | 3.5%~4.5%   |              |
| Electrolyte (*)                   | 21324-40-3/623-53-0 | 11%~14 %    |              |
| Iron(Fe)                          | 7439-89-6           | 9%~10.5%    |              |
| Chromium(Cr)                      | 7440-47-3           | 2%~2.5%     |              |
| Nickel(Ni)                        | 7440-02-0           | 0.75~1.25%  |              |

(\*) Main ingredients: Lithium hexafluorophosphate, organic carbonates.

\* The exact percentage (concentration) of composition has been withheld as a trade secret.

### Section 4. First Aid Measures

|                       |   |
|-----------------------|---|
| <b>General Advice</b> | <p>First aid is upon rupture of sealed battery.</p> <p><b>Eye contact:</b> If symptoms persist, call a physician. Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Keep eye wide open while rinsing. Remove contact lenses, if present and easy to do. Continue rinsing. Do not rub affected area.</p> <p><b>Skin contact:</b> Wash off immediately with soap and plenty of water for at least 15 minutes. In the case of skin irritation or allergic reactions see a physician. May cause an allergic skin reaction.</p> <p><b>Inhalation:</b> Remove to fresh air. If symptoms persist, call a physician. Get medical attention immediately if symptoms occur.</p> <p><b>Ingestion:</b> Do NOT induce vomiting. Rinse mouth immediately and drink plenty of water. Never give anything by mouth to an unconscious person. Call a physician.</p> |
|-----------------------|---|

## SAFETY DATA SHEET

|   |   |
|---|---|
|   | <b>Self-protection of the first aider:</b> Avoid contact with skin, eyes or clothing. Use personal protective equipment as required. Wear personal protective clothing (see section 8).   |
| <b>Most important symptoms and effects, both acute and delayed</b>                | <b>Most important symptoms and effects:</b> Itching. Coughing and/ or wheezing.   |
| <b>Indication of any immediate medical attention and special treatment needed</b> | <b>Notes to Physician:</b> Treat symptomatically. May cause sensitization of susceptible persons.   |
| <b>Section 5. Fire Fighting Measures</b>  |   |
| <b>Suitable extinguishing Media</b>   | Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.   |
| <b>Unsuitable Extinguishing Media</b>   | CAUTION: Use of water spray when fighting fire may be inefficient.  |
| <b>Specific Hazards arising from the chemical</b>                                 | Product is or contains a sensitizer. May cause sensitization by skin contact.   |
| <b>Hazardous Combustion Products</b>  | Carbon oxides.  |
| <b>Explosion Data</b>   | <b>Sensitivity to Mechanical Impact:</b> No.<br><b>Sensitivity to Static Discharge:</b> No.   |
| <b>Protective Equipment and precautions for firefighters</b>                      | As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.  |
| <b>Section 6. Accidental Release Measures</b>                                     |   |
| <b>Personal Precautions, protective equipment, and emergency procedures</b>       | <b>Personal Precautions:</b> Avoid contact with skin, eyes or clothing. Ensure adequate ventilation. Use personal protective equipment as required. Evacuate personnel to safe areas.<br><b>Other Information:</b> Refer to protective measures listed in Sections 7 and 8. |
| <b>Environmental Precautions</b>  | Refer to protective measures listed in Sections 7 and 8. Prevent further leakage or spillage if safe to do so.  |
| <b>Methods and material for containment and cleaning up</b>                       | <b>Methods for Containment:</b> Prevent further leakage or spillage if safe to do so.<br><b>Methods for cleaning up:</b> Pick up and transfer to properly labeled containers.   |

## SAFETY DATA SHEET

| Section 7 – Handling and Storage                  |   |
|---|---|
| <b>Precautions for safe handling</b>              | <b>Handling:</b> In case of rupture. Use personal protection equipment. Avoid contact with skin, eyes or clothing. Ensure adequate ventilation. Do not breathe dust/fume/gas/mist/vapors/spray. |
| <b>Conditions for safe storage, including any</b> | <b>Storage:</b> Keep containers tightly closed in a dry, cool and well-ventilated place.  |
| <b>incompatibilities</b>                          | <b>Incompatible Products:</b> Strong acids. Strong oxidizing agents. Strong bases.  |

### Section 8. Exposure Controls/Personal Protection

**Control parameters**  
**Exposure Guidelines**

| Exposure Guidelines   | ACGIH TLV  | OSHA PEL  | NIOSH IDLH  |
|---|--|---|---|
| Lithium Cobalt Oxide<br>(CoLiO <sub>2</sub> )<br>12190-79-3 | TWA: 0.02 mg/m <sup>3</sup>  | ---   | ---   |
| Copper<br>7440-50-8   | TWA:0.2mg/m <sup>3</sup><br>fume<br>TWA:1mg/m <sup>3</sup> Cu<br>dust and mist       | TWA:0.1mg/m <sup>3</sup> fume<br>TWA:1mg/m <sup>3</sup> dust and mist<br>(vacated) TWA:0.1g/m <sup>3</sup> Cu<br>dust,fume,mist   | IDLH:100mg/m <sup>3</sup> dust,fume<br>and mist<br>TWA:1 mg/m <sup>3</sup> dust and mist<br>TWA: 0.1 mg/m <sup>3</sup> fume |
| Aluminum<br>7429-90-5                                       | TWA:1mg/m <sup>3</sup><br>respirable fraction  | TWA:15mg/m <sup>3</sup> total dust<br>TWA:5mg/m <sup>3</sup> respirable fraction(vacated)<br>TWA:15mg/m <sup>3</sup> total dust(vacated)<br>TWA:5mg/m <sup>3</sup> respirable fraction(vacated)<br>TWA:5mg/m <sup>3</sup> AL Aluminum | TWA:10 mg/m <sup>3</sup> total dust<br>TWA:5mg/m <sup>3</sup> respirable<br>dust  |
| Graphite<br>7782-42-5                                       | TWA:2mg/m <sup>3</sup><br>Respirable fraction<br>all forms except<br>graphite fibers | TWA:15mg/m <sup>3</sup> total dust synthetic<br>TWA:5mg/m <sup>3</sup> respirable fraction synthetic<br>TWA:2.5mg/m <sup>3</sup> respirable dust<br>natural(vacated) TWA:10mg/m <sup>3</sup> total dust<br>synthetic                  | IDLH:1250 mg/m <sup>3</sup><br>TWA:2.5 mg/m <sup>3</sup> respirable<br>dust   |

\*ACGIH TLV: American Conference of Governmental Industrial Hygienists - Threshold Limit Value  
OSHA PEL: Occupational Safety and Health Administration - Permissible Exposure Limits NIOSH  
IDLH Immediately Dangerous to Life or Health

**Other Exposure Guidelines**

Vacated limits revoked by the Court of Appeals decision in AFL-CIO v. OSHA, 965 F.2d 962 (11th Cir., 1992) See section 15 for national exposure control parameters

|                             |                                     |
|-----------------------------|-------------------------------------|
| <b>Engineering Controls</b> | Keep away from heat and open flame. |
|-----------------------------|-------------------------------------|

## SAFETY DATA SHEET

|                               |  |
|-------------------------------|--|
| <b>Ventilation</b>            | Not necessary under conditions of normal use. In case of abuse, use adequate mechanical ventilation (local exhaust) for the battery that vent gas or fumes.  |
| <b>Respiratory Protection</b> | Not necessary under conditions of normal use. If battery is burning, leave the area immediately. During fire fighting fireman should use self-contained breathing, full-face respiratory equipment. Fires may be fought but only from safe fire fighting distance, evacuate all persons from the area of fire immediately. |
| <b>Eye Protection</b>         | Not necessary under conditions of normal use. Use safety glasses with side shields if handling a leaking or ruptured battery.  |
| <b>Body Protection</b>        | Not necessary under conditions of normal use. Use rubber apron and protective working in case of handling a leaking of ruptured battery.   |
| <b>Protective Gloves</b>      | Not necessary under conditions of normal use. Use chemical resistant rubber gloves if handling a leaking or ruptured battery.  |
| <b>Others</b>                 | Use good chemical hygiene practice. Wash hands thoroughly after cleaning-up a battery spill caused by leaking battery. No eating, drinking, or smoking in battery storage area.  |

### Section 9. Physical and Chemical Properties

#### Information on basic physical and chemical properties

|  |                   |
|--|-------------------|
| State                                  | No data available |
| Colour                                 | No data available |
| Odor                                   | No data available |
| Odor Threshold                         | No data available |
| pH                                     | No data available |
| Melting / freezing point               | No data available |
| Boiling point / boiling range          | No data available |
| Flash Point                            | No data available |
| Evaporation Rate                       | No data available |
| Flammability (solid, gas)              | No data available |
| Explosion Limits(vol% in air)          | No data available |
| Vapor pressure                         | No data available |
| Vapor density                          | No data available |
| Specific Gravity                       | No data available |
| Water Solubility                       | No data available |
| Solubility in other solvents           | No data available |
| Partition coefficient: n-octanol/water | 0.0001            |
| Autoignition temperature               | 130°C             |
| Decomposition temperature              | No data available |
| Kinematic viscosity                    | No data available |

## SAFETY DATA SHEET

|   |   |
|---|---|
| Dynamic viscosity                               | 0.0001  |
| Explosive properties                            | No data available   |
| Oxidizing Properties                            | No data available   |
| <b>Other Information</b>                        |   |
| Softening Point                                 | No data available   |
| VOC Content (%)                                 | No data available   |
| Particle Size                                   | No data available   |
| Particle Size Distribution                      | No data available   |
| <b>Section 10. Stability and Reactivity</b>     |   |
| <b>Stability</b>                                | Stable  |
| <b>Conditions to Avoid</b>                      | Do not heat, throw into fire, disassemble, short circuit, immerse in water or overcharge, etc.  |
| <b>Incompatibility</b>                          | None during normal operation. Avoid exposure heat, open flame and corrosives.   |
| <b>Hazardous Polymerization</b>                 | Hazardous polymerization does not occur.  |
| <b>Hazardous Decomposition Products</b>         | The battery may release irritative gas once the electrolyte leakage.  |
| <b>Section 11. Toxicological Information</b>    |   |
| <b>Information on likely routes of exposure</b> |   |
| <b>Product Information</b>                      | Product does not present an acute toxicity hazard based on known or supplied information. In case of rupture:.  |
| <b>Inhalation</b>                               | Specific test data for the substance or mixture is not available. May cause irritation of respiratory tract.  |
| <b>Eye Contact</b>                              | Specific test data for the substance or mixture is not available. Expected to be an irritant based on components. Irritating to eyes. May cause redness, itching, and pain. May cause temporary eye irritation. |
| <b>Skin Contact</b>                             | Specific test data for the substance or mixture is not available. Expected to be an irritant based on components. Irritating to skin. Prolonged contact may cause redness and irritation.                       |
| <b>Ingestion</b>                                | Specific test data for the substance or mixture is not available. Ingestion may cause irritation to mucous membranes. Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhea.           |
| <b>Component Information</b>                    |   |
| <b>Information on toxicological effects</b>     | <b>Symptoms:</b> Erythema (skin redness). May cause redness and tearing of the eyes. Itching. Rashes. Hives.  |

**SAFETY DATA SHEET**

|   |  |   |            |             |
|---|--|---|------------|-------------|
| <b>Delayed and immediate effects as well as chronic effects from short and long-term exposure</b>   |  | <p><b>Sensitization:</b> May cause sensitization of susceptible persons. May cause sensitization by skin contact.</p> <p><b>Mutagenic Effects:</b> No information available.</p> <p><b>Carcinogenicity:</b> The table below indicates whether each agency has listed any ingredient as a carcinogen</p> |            |             |
| <b>Chemical Name</b>  | <b>ACGIH</b>   | <b>IARC</b>   | <b>NTP</b> | <b>OSHA</b> |
| Lithium Cobalt Oxide (CoLiO2)<br>12190-79-3   | A3   | Group 2B  |            | X           |
| <p><b>ACGIH (American Conference of Governmental Industrial Hygienists)</b><br/>A3 - Animal Carcinogen</p> <p><b>IARC (International Agency for Research on Cancer)</b><br/>Group 1 - Carcinogenic to Humans<br/>Group 2B - Possibly Carcinogenic to Humans<br/>Group 3 - Not Classifiable as to Carcinogenicity in Humans</p> <p><b>OSHA (Occupational Safety and Health Administration of the US Department of Labor)</b><br/>X – Present</p> |  |   |            |             |
| <b>Reproductive Toxicity</b>  | No information available.  |   |            |             |
| <b>STOT - single exposure</b>   | No information available.  |   |            |             |
| <b>STOT – repeated exposure</b>   | Causes damage to organs through prolonged or repeated exposure. Based on classification criteria from the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200), this product has been determined to cause systemic target organ toxicity from chronic or repeated exposure. (STOT RE). |   |            |             |
| <b>Chronic Toxicity</b>   | Contains a known or suspected carcinogen. Avoid repeated exposure. Prolonged exposure may cause chronic effects. May cause adverse liver effects.  |   |            |             |
| <b>Target Organ Effects</b>   | Respiratory system. Eyes. Skin. Gastrointestinal tract (GI). Central Vascular System (CVS).Kidney. Liver. Lungs. Heart.  |   |            |             |
| <b>Aspiration Hazard</b>  | No information available.  |   |            |             |
| <b>Numerical measures of toxicity Product Information</b>   |  |   |            |             |
| <b>The values which are on the right are calculated based on chapter 3.1 of the GHS document.</b>   | <p><b>ATEmix (oral)</b></p> <p><b>ATEmix (dermal)</b></p> <p><b>ATEmix (inhalation-dust/mist)</b></p>  |   |            |             |
| <b>Section 12. Ecological Information</b>   |  |   |            |             |



## SAFETY DATA SHEET

**Ecotoxicity**

Very toxic to aquatic life with long lasting effects

| Chemical Name       | Toxicity to Algae   | Toxicity to Fish   | Toxicity to Microorganisms | Daphnia Magna (Water flea) |
|---------------------|---|--|----------------------------|----------------------------|
| Copper<br>7440-50-8 | 96h EC50: 0.031 - 0.054 mg/L (Pseudokirchneriella subcapitata) 72h EC50: 0.0426 - 0.0535 mg/L (Pseudokirchneriella subcapitata) | 96h LC50: 0.0068 - 0.0156 mg/L (Pimephales promelas)<br>96h LC50: = 0.112 mg/L (Poecilia reticulata)<br>96h LC50: = 0.3 mg/L (Cyprinus carpio)<br>96h LC50: = 0.8mg/L (Cyprinus carpio)<br>96h LC50: = 1.25 mg/L (Lepomis macrochirus)<br>96h LC50: =0.052 mg/L (Oncorhynchus mykiss)<br>96h LC50: = 0.2mg/L (Pimephales promelas)<br>96h LC50: < 0.3 mg/L (Pimephales promelas) |                            | 48h EC50: = 0.03 mg/L      |

|                                      |                           |
|--------------------------------------|---------------------------|
| <b>Persistence and Degradability</b> | No information available. |
| <b>Bioaccumulation</b>               | No information available  |
| <b>Other adverse effects</b>         | No information available  |

### Section 13. Disposal Considerations

**Waste treatment methods**

**Disposal methods:** This material, as supplied, is not a hazardous waste according to Federal regulations (40CFR 261). This material could become a hazardous waste if it is mixed with or otherwise comes in contact with a hazardous waste, if chemical additions are made to this material, or if the material is processed or otherwise altered. Consult 40 CFR 261 to determine whether the altered material is a hazardous waste. Consult the appropriate state, regional, or local regulations for additional requirements.

**Contaminated Packaging:** Dispose of in accordance with federal, state and local regulations.

**California Hazardous Waste Codes 141**

This product contains one or more substances that are listed with the State of California as a hazardous waste

| Chemical Name                               | California Hazardous Waste |
|---|----------------------------|
| Lithium Cobalt Oxide (CoLiO2)<br>12190-79-3 | Toxic                      |
| Copper<br>7440-50-8                         | Toxic                      |
| Aluminum<br>7429-90-5                       | Ignitable powder           |

### Section 14. Transport Information

The Rechargeable Lithium Ion Battery stated in appendix is made in compliance to packing Instruction of PI965

**SAFETY DATA SHEET**

section IB or PI966 section II or PI967 section II stated in the latest edition of the IATA Dangerous Goods Regulations.

With regard to transportation, following regulations are cited and considered:

- The International Civil Aviation Organization (ICAO) Technical Instructions, packing instructions of PI 965 section IB or PI 966 section II or PI 967 section II (2019-2021 Edition).
- The International Air transport Association (IATA) Dangerous Goods Regulations, packing instructions of 965 section IB or 966 section II or 967 section II (62<sup>nd</sup> Edition, 2021).
- Special provision 188 of the International Maritime Dangerous Goods (IMDG) Code (Amendment 39-18 Edition).
- The US Hazardous Materials Regulation 49 CFR (Code of Federal Regulations), sections 173-185 Lithium batteries and cells.
- UN Recommendations on transportation of Dangerous Goods, UN38.3 Manual of Tests and Criteria for lithium battery

These products are properly classified, described, packaged, marked, and labeled, and are in proper condition for transportation according to all the applicable international and national governmental regulations, not limited to the above mentioned. We further certify that the enclosed products have been tested and fulfilled the requirements and conditions in accordance with UN Recommendations (T1 – T8) on the Transport of Dangerous Goods Model Regulations and the Manual of Tests and Criteria.

- UN Number: UN3480, UN3481

**Test results of the UN Recommendation on the Transport of Dangerous Goods**

| <b>Manual of Test and Criteria (38.3 Lithium battery)</b> |                        |                     |               |
|---|------------------------|---------------------|---------------|
| <b>No.</b>  | <b>Test items</b>      | <b>Test results</b> | <b>Remark</b> |
| T1  | Altitude simulation    | Pass                |               |
| T2  | Thermal test           | Pass                |               |
| T3  | Vibration              | Pass                |               |
| T4  | Shock                  | Pass                |               |
| T5  | External short circuit | Pass                |               |
| T6  | Impact / Crush         | Pass                |               |
| T7  | Overcharge             | Pass                |               |
| T8  | Forced discharge       | Pass                |               |

**Additional Requirements for air transport:**

1. Cells and batteries must be protected so as to prevent short circuits. This includes protection against contact with conductive materials within the same packaging that could lead to a short circuit.
2. Cells and batteries must be manufactured under a quality management program.
3. The Watt-hour rating must be marked on the outside of the battery case except those manufactured before 1 January 2009.
4. Cells and batteries must be packed in strong outer packaging. (applicable to PI 965 only)
5. Maximum number of cells per package must not be more than 8 cells. (applicable to PI 965 only)
6. Cells and batteries must be packed in inner packaging that completely enclose the cell or battery. To provide protection

## SAFETY DATA SHEET

from damage or compression to the batteries, the inner packaging must be placed in a strong rigid outer packaging of one of the packaging types shown below.

7. Each package must be capable of withstanding a 1.2 m drop test in any orientation without

(applicable to PI 965 only):

- damage to cells or batteries contained therein;
- shifting of the contents so as to allow battery to battery (or cell to cell) contact;
- release of contents.

8. Each consignment must be accompanied with a document with an indication that:

- the package contains lithium ion cells or batteries;
- the package must be handled with care and that a flammability hazard exists if the package is damaged;
- special procedures must be followed in the event the package is damaged, to include inspection and repacking if necessary; and a telephone number for additional information.

9. Each package must be labeled with a lithium battery handling label (Figure 7.4.H).

10. A Shipper's Declaration for Dangerous Goods is not required.

11. The words "Lithium ion batteries in compliance with Section II of PI 965" must be included on the air waybill, when an air waybill is used. The information should be shown in the "Nature and Quantity of Goods" box of the air waybill. (applicable to PI 965 only)

12. Any person preparing or offering cells for transport must receive adequate instruction on these requirements commensurate with their responsibilities.

13. The equipment must be secured against movement within the outer packaging and must be equipped with an effective means of preventing accidental activation. (applicable to PI 966 only)

14. The maximum number of batteries in each package must be the minimum number required to power the equipment plus two spares. (applicable to PI 966 only)

15. The words "Lithium ion batteries in compliance with Section II of PI 966" must be included on the air waybill, when an air waybill is used. The information should be shown in the "Nature and Quantity of Goods" box of the air waybill. (applicable to PI 966 only).

### Section 15. Regulatory Information

#### Law Information

《California Proposition 65》

《Canadian Domestic Substances List/Non-Domestic Substances List》 (DSL/NDSL)

《Classification and code of dangerous goods》

《Code of Federal Regulations》 (CFR)

《Consumer Product Safety Act》 (CPSA)

《Dangerous Goods Regulation 62<sup>nd</sup> Edition》

《Federal Environmental Pollution Control Act》 (FEPCA)

《International Maritime Dangerous Goods 39-18 Edition》

《Occupational Safety and Health Act》 (OSHA)

《Recommendations on Transport of Dangerous Goods Model Regulations》

《Resource Conservation and Recovery Act》 (RCRA)

《Safety Drinking Water Act》 (CWA)

《Superfund Amendments and Reauthorization Act III(302/311/312/313)》 (SARA)

## SAFETY DATA SHEET

《Technical Instructions for the Safe Transport of Dangerous Goods》

《The Oil Pollution Act》 (OPA)

《Toxic Substances Control Act》 (TSCA)

《US Federal Regulations》

**SARA 313**

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372

| Chemical Name                             | CAS No     | Weight-% | SARA 313 – Threshold Values % |
|---|------------|----------|-------------------------------|
| Lithium Cobalt Oxide(LiCoO <sub>2</sub> ) | 12190-79-3 | 40%~44%  | 0.1                           |
| Copper Foil                               | 7440-50-8  | 8%~11%   | 1.0                           |
| Aluminum Foil                             | 7429-90-5  | 4%~6%    | 1.0                           |

**SARA 311/312 Hazard Categories**

|                                   |    |
|-----------------------------------|----|
| Acute Health Hazard               | No |
| Chronic Health Hazard             | No |
| Fire Hazard                       | No |
| Sudden release of pressure hazard | No |
| Reactive Hazard                   | No |

**CWA (Clean Water Act)**

This product contains the following substances which are regulated pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42)

| Chemical Name            | CWA -Reportable Quantities | CWA - Toxic Pollutants | CWA - Priority Pollutants | CWA -Hazardous Substances |
|--------------------------|----------------------------|------------------------|---------------------------|---------------------------|
| Copper Foil<br>7440-50-8 |                            | ×                      | ×                         |                           |

**CERCLA**

This material, as supplied, contains one or more substances regulated as a hazardous substance under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40CFR 302)

| Chemical Name            | Hazardous Substances RQs | Extremely Hazardous Substances RQs | RQ   |
|--------------------------|--------------------------|------------------------------------|--|
| Copper Foil<br>7440-50-8 | 5000lb                   |                                    | RQ 5000 lb final RQ<br>RQ 2270 kg final RQ |

**U.S. State Right-to-Know Regulations**

| Chemical Name  | New Jersey | Massachusetts | Pennsylvania | Rhode Island | Illinois |
|--|------------|---------------|--------------|--------------|----------|
| Lithium Cobalt Dioxide<br>(LiCoO <sub>2</sub> ) 12190-79-3 | X          |               | X            | X            | X        |
| Graphite 7782-42-5   | X          | X             | X            |              |          |
| Copper<br>7440-50-8  | X          | X             | X            | X            | X        |
| Aluminum<br>7429-90-5                                      | X          | X             | X            | X            |          |

## SAFETY DATA SHEET

**International Regulations**

**Mexico**

**National occupational exposure limits**

| Component               | Carcinogen Status | Exposure Limits  |
|-------------------------|-------------------|--|
| Copper Foil 7440-50-8   |                   | Mexico: TWA=1 mg/m <sup>3</sup><br>Mexico: TWA=0.2 mg/m <sup>3</sup><br>Mexico: STEL=2 mg/m <sup>3</sup> |
| Aluminum Foil 7429-90-5 |                   | Mexico: TWA=10mg/m <sup>3</sup>  |
| Graphite 7782-42-5      |                   | Mexico: TWA= 2 mg/m <sup>3</sup>   |

*Mexico - Occupational Exposure Limits – Carcinogens*

**Canada**

**WHMIS Hazard Class**

Non-controlled

| Chemical Name | NPRI |
|---------------|------|
| Aluminum      | X    |

In accordance with all Federal, State and local laws.

### Section 16. Other Information

| NFPA | Health Hazards 1 | Flammability 0 | Instability 0 | Physical and<br>Chemical Hazards -<br>Personal Protection X |
|------|------------------|----------------|---------------|---|
| HMIS | Health Hazards 0 | Flammability 0 | Instability 0 |   |

**Revision Date:** 2021-01-01

**Revision Note:** No information available

**Disclaimer**

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

---End of Safety Data Sheet---